




### Standard



### Optional



### 2S

	4075	2950	2050	1500	kg
	2.75	3.95	5.55	7.47	m
1555 kg 3425 lb	8980	6500	4515	3305	lb
	9'	12'11"	18'2"	24'6"	ft

### 3S

	3945	2805	1940	1400	1095	kg
	2.75	4.02	5.62	7.57	9.55	m
1685 kg 3710 lb	8695	6180	4275	3085	2410	lb
	9'	13'2"	18'5"	24'10"	31'3"	ft

### 4S

	3865	2700	1850	1300	995	805	kg
	2.75	4.09	5.69	7.63	9.63	11.68	m
1810 kg 3990 lb	8520	5950	4075	2865	2190	1770	lb
	9'	13'5"	18'8"	25'	31'7"	38'3"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
2S	11,64	400	2275	2495	780	4555 5955	13
3S	11,28	400	2275	2495	780	4555 5955	13
4S	11,05	400	2275	2495	780	4555 5955	13

MODEL							
	lb*ft	(°)	in	in	in	in	lb
2S	84220	400	90	98	31	179 234	28700
3S	81620	400	90	98	31	179 234	28700
4S	79950	400	90	98	31	179 234	28700