




Standard



Optional



2S

	4950	3600	2570	1890	kg
	2.73	3.86	5.36	7.29	m
1725 kg 3800 lb	10910	7935	5665	4165	lb
	8'11"	12'7"	17'7"	23'11"	ft

3S

	4850	3470	2460	1780	1385	kg
	2.73	3.94	5.44	7.36	9.36	m
1860 kg 4100 lb	10690	7645	5420	3920	3050	lb
	8'11"	12'11"	17'10"	24'1"	30'8"	ft

4S

	4700	3310	2310	1650	1260	1020	kg
	2.73	4.01	5.51	7.44	9.44	11.49	m
	10360	7295	5090	3635	2775	2245	lb
	8'11"	13'1"	18'	24'4"	30'11"	37'8"	ft

3S+JIB 3S

	720	640	460	350	kg
	12.03	13.41	14.82	16.25	m
2245 kg 4945 lb	1585	1410	1010	770	lb
	39'5"	43'11"	48'7"	53'3"	ft

	940	710	480	380	kg
	5.21	6.60	8.01	9.44	m
	2070	1565	1055	835	lb
	17'1"	21'7"	26'3"	30'11"	ft

4S+JIB 2S

	540	485	435	kg
	14.01	15.40	16.82	m
2350 kg 5180 lb	1190	1065	955	lb
	45'11"	50'6"	55'2"	ft

	850	660	485	kg
	5.51	6.90	8.32	m
	1870	1455	1065	lb
	18'	22'7"	27'3"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
2S	13,91	400	2295	2495	810	5960	15
3S	13,67	400	2295	2495	810	5960	15
4S	13,28	400	2295	2495	810	5960	15
3S+JIB 3S	13,67	400	2295	2505	910	5960	15
4S+JIB 2S	13,28	400	2295	2505	910	5960	15

MODEL							
	lb*ft	(°)	in	in	in	in	lb
2S	100650	400	90	98	32	235	33100
3S	98910	400	90	98	32	235	33100
4S	96090	400	90	98	32	235	33100
3S+JIB 3S	98910	400	90	98	36	235	33100
4S+JIB 2S	96090	400	90	98	36	235	33100