


165.00 C


EFFER
165.00 C



Standard



Optional



3S

	5100	3660	2600	1880	1470	kg
	2.73	3.94	5.54	7.36	9.36	m
1895 kg 4175 lb	11240	8065	5730	4140	3240	lb
	8'11"	12'11"	18'2"	24'1"	30'8"	ft

4S

	4700	3500	2460	1755	1340	1090	kg
	2.73	4.01	5.51	7.44	9.44	11.49	m
2015 kg 4440 lb	10360	7715	5420	3865	2950	2400	lb
	8'11"	13'1"	18'	24'4"	30'11"	37'8"	ft

3S+JIB 3S

	790	685	480	365	kg
	12.03	13.41	14.82	16.25	m
2280 kg 5025 lb	1740	1510	1055	800	lb
	39'5"	43'11"	48'7"	53'3"	ft

	1020	780	530	400	kg
	5.21	6.60	8.01	9.44	m
	2245	1715	1165	880	lb
	17'1"	21'7"	26'3"	30'11"	ft

4S+JIB 2S

	600	535	460	kg
	14.01	15.40	16.82	m
2385 kg 5255 lb	1320	1175	1010	lb
	45'11"	50'6"	55'2"	ft

	900	710	510	kg
	5.51	6.90	8.32	m
	1980	1565	1120	lb
	18'	22'7"	27'3"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
3S	14,42	400	2295	2495	810	5960	15
4S	14,05	400	2295	2495	810	5960	15
3S+JIB 3S	14,42	400	2295	2505	910	5960	15
4S+JIB 2S	14,05	400	2295	2505	910	5960	15

MODEL							
	lb*ft	(°)	in	in	in	in	lb
3S	104340	400	90	98	32	235	33100
4S	101660	400	90	98	32	235	33100
3S+JIB 3S	104340	400	90	99	36	235	33100
4S+JIB 2S	101660	400	90	99	36	235	33100