




Standard



Optional



2S

	5505	3625	2365	1765	kg
	2.66	4.30	6.40	8.50	m
1980 kg 4365 lb	12135	7990	5210	3890	lb
	8'8"	14'1"	20'11"	27'10"	ft

3S

	5355	3455	2255	1655	1295	kg
	2.66	4.37	6.47	8.57	10.67	m
2155 kg 4750 lb	11805	7615	4970	3645	2850	lb
	8'8"	14'4"	21'2"	28'1"	35'	ft

4S

	5220	3290	2125	1490	1150	945	kg
	2.66	4.45	6.55	8.65	10.75	12.85	m
2305 kg 5080 lb	11505	7250	4680	3280	2535	2080	lb
	8'8"	14'7"	21'5"	28'4"	35'3"	42'1"	ft

5S

	5105	3145	1985	1395	1060	860	730	kg
	2.66	4.53	6.63	8.73	10.83	12.93	15.03	m
2410 kg 5310 lb	11250	6930	4375	3075	2335	1895	1605	lb
	8'8"	14'10"	21'9"	28'7"	35'6"	42'5"	49'3"	ft

6S

	5005	3045	1890	1310	975	770	640	555	kg
	2.66	4.60	6.70	8.80	10.90	13.00	15.10	17.20	m
2515 kg 5540 lb	11030	6710	4165	2885	2145	1695	1410	1220	lb
	8'8"	15'1"	21'11"	28'10"	35'9"	42'7"	49'6"	56'5"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
2S	15,58	400	2245	2425	880	4490 5690	18
3S	15,11	400	2245	2425	880	4490 5690	18
4S	14,64	400	2245	2425	880	4490 5690	18
5S	14,24	400	2245	2425	1030	4490 5690	18
6S	14,01	400	2245	2425	1030	4490 5690	18

MODEL							
	lb*ft	(°)	in	in	in	in	lb
2S	112730	400	88	95	35	177 224	39700
3S	109330	400	88	95	35	177 224	39700
4S	105930	400	88	95	35	177 224	39700
5S	103030	400	88	95	41	177 224	39700
6S	101370	400	88	95	41	177 224	39700