




### Standard



### Optional



### 85

	21650	14700	10750	8240	6630	5500	4700	4100	3660	kg
	5.41	7.6	9.87	12.22	14.53	16.84	19.17	21.59	24.05	m
14300 kg	47725	32405	23695	18165	14615	12125	10360	9035	8065	lb
31525 lb	178"	24'11"	32'4"	40'1"	47'8"	55'2"	62'10"	70'9"	78'10"	ft

### 86

### 8S+JIB 6S

	1610	1500	1380	1290	1210	1140	1070	kg
	27.18	28.64	30.21	31.82	33.45	35.14	36.85	m
16280 kg	3545	3305	3040	2840	2655	2510	2355	lb
35890 lb	89'2"	93'11"	99'1"	104'4"	109'8"	115'3"	120'10"	ft

20°

	7800	5900	4100	3100	2450	2000	1710	kg
	11.22	12.66	14.23	15.84	17.47	19.16	20.87	m
	17195	13005	9035	6830	5400	4405	3765	lb
	36'9"	41'6"	46'8"	51'11"	57'3"	62'10"	68'5"	ft

### 8S+JIB L 6S

	1130	1050	940	820	750	700	640	kg
	28.30	30.74	33.14	35.23	37.13	39.13	41.03	m
16625 kg	2490	2310	2070	1805	1650	1540	1410	lb
36650 lb	92'10"	100'10"	108'8"	115'7"	121'9"	128'4"	134'7"	ft

20°

	6000	3300	2185	1620	1360	1110	980	kg
	12.29	14.73	17.13	19.22	21.11	23.12	25.01	m
	13225	7275	4815	3570	2995	2445	2160	lb
	40'3"	48'3"	56'2"	63'	69'3"	75'10"	82'	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
85	117,15	∞	2785	2550	4115	10100	32
8S+JIB 6S	117,15	∞	2875	2550	4115	10100	32
8S+JIB L 6S	117,15	∞	2875	2550	4115	10100	32

MODEL							
	lb*ft	(°)	in	in	in	in	lb
85	847640	∞	110	100	162	398	70500
8S+JIB 6S	847640	∞	113	100	162	398	70500
8S+JIB L 6S	847640	∞	113	100	162	398	70500