



Standard



Optional



1S

	2835	1950	1380	kg
	2.55	3.82	5.42	m
825 kg 1815 lb	6250	4295	3040	lb
	8'4"	12'6"	17'9"	ft

2S

	2725	1835	1290	985	kg
	2.55	3.91	5.51	7.21	m
905 kg 1995 lb	6005	4045	2840	2170	lb
	8'4"	12'9"	18'	23'7"	ft

3S

	2645	1740	1200	900	725	kg
	2.55	4.00	5.60	7.30	9.00	m
970 kg 2135 lb	5830	3835	2645	1980	1595	lb
	8'4"	13'1"	18'4"	23'11"	29'6"	ft

4S

	2545	1640	1110	815	640	535	kg
	2.55	4.09	5.69	7.39	9.09	10.79	m
1025 kg 2255 lb	5610	3615	2445	1795	1410	1175	lb
	8'4"	13'5"	18'8"	24'2"	29'9"	35'4"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
1S	7,48	380	2095	2215	635	3382 4857	9
2S	7,17	380	2095	2215	635	3382 4857	9
3S	6,96	380	2095	2240	635	3382 4857	9
4S	6,71	380	2095	2300	635	3382 4857	9

MODEL							
	lb*ft	(°)	in	in	in	in	lb
1S	54120	380	82	87	25	133 191	19800
2S	51880	380	82	87	25	133 191	19800
3S	50360	380	82	88	25	133 191	19800
4S	48550	380	82	90	25	133 191	19800